NSN 5306-00-468-6802

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-468-6802 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** Between 3.487 inches and 3.527 inches **Head Style:** Hexagon **Head Height:** 0.180 inches Width Between Flats: Between 0.428 inches and 0.438 inches **First Diameter From Head:** Between 0.185 inches and 0.190 inches **Second Diameter From Head:** Between 0.367 inches and 0.375 inches Third Diameter From Head: Between 0.185 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 2.685 inches and 2.715 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 2.805 inches and 2.835 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 3.107 inches and 3.147 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Material Specification:** Mil-t-9047 military specification single material response **Surface Treatment:** Silver **Surface Treatment Specification:** Ams 2411 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

She N/a

NSN 5306-00-468-6802

Externally Relieved Body Bolt - Page 2 of 2



H	ni	it	Of	м	e۵	CI.	ır۵	•
·	•••	•	v.		Cu	30		•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-t-9047 spec.