NSN 5306-00-469-3566

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-469-3566



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.309 inches and 0.359 inches

Fastener Length:

Between 1.131 inches and 1.161 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.265 inches and 0.285 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.340 inches and 0.350 inches

Extended Washer Thickness:

Between 0.054 inches and 0.074 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-00-469-3566

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

