

View Online at <https://aerobasegroup.com/nsn/5306-00-469-3629>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.451 inches and 0.511 inches

Fastener Length:

Between 1.278 inches and 1.308 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.797 inches and 0.827 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

140000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.068 inches first hole and 1.088 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1003 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0