## NSN 5306-00-469-5339

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-469-5339 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.500 inches **Fastener Length:** Between 2.125 inches and 2.375 inches **Head Style:** Hexagon **Head Height:** Between 0.378 inches and 0.403 inches Width Between Flats: Between 0.906 inches and 0.937 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 0.625 inches and 0.875 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 11 Min. Tensile Strength (psi): 75000 pounds per square inch Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 or steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5306-00-469-5339** Machine Bolt - Page 2 of 2



Fiig:

A003b0