## NSN 5306-00-470-3071

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-470-3071

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.778 inches and 0.798 inches
Fastener Length:
1.913 inches
Head Style:
Double hexagon w/hole
Head Height:
0.504 inches
Width Between Flats:
Between 0.533 inches and 0.564 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
0.123 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium or chromate
Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification all treatment responses

## NSN 5306-00-470-3071

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0