## NSN 5306-00-470-5408

Machine Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-470-5408

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.500 inches and 0.579 inches
Fastener Length:
Between 4.328 inches and 4.375 inches
Head Style:
Hexagon
Head Height:
Between 0.172 inches and 0.204 inches
Width Between Flats:
Between 0.490 inches and 0.502 inches
Locking Feature:
Pellet threads
Thread Diameter:
0.312 inches
Grip Length:
Between 3.796 inches and 3.828 inches
Features Provided:
Finished head
Finished head  Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating:
Thready Qty Per Inch (tpi):  24  Min. Tensile Strength (psi):  125000 pounds per square inch  Hardness Rating:  26.0 rockwell c and 32.0 rockwell c
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material:
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material:  Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material:  Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037  Thread Series Designator:
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037  Thread Series Designator: Unf
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material:  Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037  Thread Series Designator: Unf  Shelf Life:
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037  Thread Series Designator: Unf Shelf Life: N/a
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037  Thread Series Designator: Unf Shelf Life: N/a
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c  Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037  Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure:
Thready Qty Per Inch (tpi): 24  Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: