Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-470-5446

| Thread Class:   |   |
|-----------------|---|
| За              |   |
| Thread Directi  | on:   |
| Right-hand      |   |
| Thread Length   | 1:  |
|                 | inches and 0.544 inches                                     |
| Fastener Leng   | jth:  |
| Between 1.187   | inches and 1.234 inches                                     |
| Head Style:     |   |
| Hexagon         |   |
| Head Height:    |   |
| Between 0.203   | inches and 0.235 inches                                     |
| Width Betwee    | n Flats:  |
| Between 0.553   | inches and 0.565 inches                                     |
| First Diameter  | From Head:  |
| 0.312 inches    |   |
| Distance From   | n Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.690 inches    |   |
| Thread Diame    | ter:  |
| 0.375 inches    |   |
| Thready Qty P   | er Inch (tpi):  |
| 24              |   |
| Externally Rel  | ieved Body Diameter Quantity:                               |
| 1               |   |
| Material:       |   |
| Steel comp 437  | I   |
| Material Speci  | fication:   |
| Mil-s-18732 mi  | litary specification single material response               |
| Thread Series   | Designator:   |
| Unf             |   |
| Shelf Life:     |   |
| N/a             |   |
| Unit Of Measu   | re:   |
|                 |   |
| Demilitarizatio | in:   |
| No              |   |
| Fiig:           |   |
| A003b0          |   |
| Mil-std (milita |   |
| Mil-s-18732 sp  | ec.   |