

View Online at <https://aerobasegroup.com/nsn/5306-00-470-8728>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.403 inches and 0.450 inches

Fastener Length:

Between 1.653 inches and 1.700 inches

Head Style:

Double hexagon

Head Height:

0.210 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

1.250 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

156000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.520 inches first hole and 1.552 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Stsbs001 fscm 98897 mfr ref single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Stsbs001 fscm 98897 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0