

View Online at <https://aerobasegroup.com/nsn/5306-00-470-8728>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.403 inches and 0.450 inches

**Fastener Length:**

Between 1.653 inches and 1.700 inches

**Head Style:**

Double hexagon

**Head Height:**

0.210 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.250 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

156000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.520 inches first hole and 1.552 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp h11

**Material Specification:**

Stsbs001 fscm 98897 mfr ref single material response

**Surface Treatment:**

Nickel and cadmium and chromate

**Surface Treatment Specification:**

Stsbs001 fscm 98897 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0