NSN 5306-00-472-5238

Eye Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-472-5238

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.890 inches and 0.937 inches
Eye Inside Diameter:
Between 0.500 inches and 0.503 inches
Shoulder Thickness:
0.125 inches
Shank Length:
Between 1.140 inches and 1.187 inches
Eye Stock Thickness:
Between 0.370 inches and 0.380 inches
Shoulder Diameter:
1.188 inches
Overall Length:
Between 2.749 inches and 2.796 inches
Thread Diameter:
0.562 inches
Thready Qty Per Inch (tpi):
* * * * * * * * * * * * * * * * * * * *
18
18
18 Min. Tensile Strength (psi):
18 Min. Tensile Strength (psi): 125000 pounds per square inch
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project Material:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project Material: Steel comp 431 Material Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project Material: Steel comp 431
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project Material: Steel comp 431 Material Specification: Mil-s-18732 military specification single material response Surface Treatment:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project Material: Steel comp 431 Material Specification: Mil-s-18732 military specification single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Distance From Center Of Eye To Shank End: 0.938 inches Eye Outside Width: 1.188 inches Product Name: Navy special project Material: Steel comp 431 Material Specification: Mil-s-18732 military specification single material response Surface Treatment:

Style Designator:

Round, closed w/shoulder

NSN 5306-00-472-5238

Eye Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: No

Mil-std (military Standard):

Mil-s-18732 spec.