NSN 5306-00-472-5392

Shear Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-00-472-5392

Thread Direction:
Right-hand
Thread Length:
Between 0.502 inches and 0.522 inches
Fastener Length:
1.387 inches
Head Style:
Double hexagon w/hole
Head Height:
0.300 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
0.069 inches
Hole Diameter:
0.037 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium and chromate

NSN 5306-00-472-5392

Shear Bolt - Page 2 of 2



Surface Treatment S	Specification:
---------------------	----------------

Qq-p-416 type 2 class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0