NSN 5306-00-474-1519

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-474-1519 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.238 inches and 0.248 inches **Fastener Length:** Between 2.145 inches and 2.161 inches **Head Style:** Flat chamfer **Head Diameter:** 1.125 inches **Head Height:** 0.220 inches **Shoulder Diameter:** 0.687 inches first shoulder **Shoulder Length:** 1.722 inches first shoulder and 1.728 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.104 inches first hole and 0.109 inches first hole **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.083 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 8740 **Material Specification:** Mil-s-6049 cond c4 military specification single material response **Surface Treatment:** Chromium **Surface Treatment Specification:** Mil-p-6871 type 2 cl a military specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5306-00-474-1519

Shoulder Bolt - Page 2 of 2



U	ni	t	O:	F	м	e	а	s	u	r	e	:
_	• • •	•	_	•	•••	_	•	_	•	•	•	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.