Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-475-9603

-	Thread Class:
	Ba
	Thread Direction:
	Right-hand
	Fhread Length:
	).344 inches
	Fastener Length:
	2.203 inches
	lead Style:
I	Round w/wrench flats
I	Head Diameter:
	I.125 inches
I	Head Height:
(	0.187 inches
	Nidth Between Flats:
(	0.990 inches
;	Shank Unthreaded Hole Diameter:
(	0.156 inches first hole
(	Concentric Hole Diameter:
(	0.312 inches
-	Thread Diameter:
(	0.625 inches
-	Thready Qty Per Inch (tpi):
	18
I	Min. Tensile Strength (psi):
	180000 pounds per square inch
	Distance From Head Largest Bearing Surface To Shank Hole Center:
	2.047 inches first hole
	Material:
	Steel comp e4340
	Material Specification:
	Ail-s-5000 military specification single material response
	Surface Treatment:
	Surface Treatment Specification:
	Qq-p-416, type 1, cl 2 federal specification single treatment response
	Style Designator:
	Concentric hole unthreaded
	Fhread Series Designator:
	Jnf
	Shelf Life:
I	√a

Internally Relieved Body Bolt - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.