

View Online at <https://aerobasegroup.com/nsn/5306-00-476-2834>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.140 inches

Fastener Length:

5.300 inches

Head Style:

Hexagon

Head Height:

0.300 inches

Width Between Flats:

1.650 inches

Shoulder Diameter:

Between 1.123 inches and 1.124 inches

Shoulder Length:

Between 4.065 inches and 4.070 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Concentric Hole Depth:

3.750 inches

Concentric Hole Diameter:

0.630 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.090 inches first hole

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium

Style Designator:

Counterbore unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.