

View Online at <https://aerobasegroup.com/nsn/5306-00-477-0211>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.514 inches and 0.574 inches

Fastener Length:

Between 2.341 inches and 2.371 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 1.797 inches and 1.827 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

140000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.114 inches first hole and 2.134 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas1004 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.