## NSN 5306-00-477-2356

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-477-2356 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.450 inches and 0.460 inches **Fastener Length:** 1.560 inches **Head Style:** Round w/wrench flats chamfered **Head Diameter:** 0.750 inches **Head Height:** 0.219 inches Width Between Flats: 0.560 inches First Diameter From Head: Between 0.4547 inches and 0.4550 inches **Second Diameter From Head:** Between 0.300 inches and 0.310 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.700 inches and 0.720 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.100 inches and 1.110 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 32.0 rockwell c and 36.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-00-477-2356

Externally Relieved Body Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0