

View Online at <https://aerobasegroup.com/nsn/5306-00-479-5178>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.707 inches and 0.757 inches

**Fastener Length:**

Between 2.217 inches and 2.247 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.435 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Extended Washer Diameter:**

Between 0.740 inches and 0.750 inches

**Extended Washer Thickness:**

Between 0.089 inches and 0.109 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.490 inches and 1.510 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Material:**

Steel

**Material Specification:**

H-11 stsb002, fscm 98897 mfr ref single material response

**Surface Treatment:**

Nickel and cadmium and chromate

**Surface Treatment Specification:**

Stsb002, lockheed-georgia co mfr ref all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0