

View Online at <https://aerobasegroup.com/nsn/5306-00-481-2217>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.380 inches

**Fastener Length:**

Between 4.487 inches and 4.527 inches

**Head Style:**

Hexagon

**Head Height:**

0.180 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**First Diameter From Head:**

Between 0.185 inches and 0.190 inches

**Second Diameter From Head:**

Between 0.367 inches and 0.375 inches

**Third Diameter From Head:**

Between 0.185 inches and 0.190 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 3.685 inches and 3.715 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 3.805 inches and 3.835 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 4.107 inches and 4.147 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

3

**Material Specification:**

Mil-t-9047 military specification single material response

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2411 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-t-9047 spec.