# NSN 5306-00-481-9808

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-481-9808



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.812 inches and 0.872 inches

## Fastener Length:

Between 5.202 inches and 5.232 inches

#### Head Style:

Hexagon

Head Height:

Between 0.265 inches and 0.297 inches

## Width Between Flats:

Between 0.741 inches and 0.751 inches

# **Thread Diameter:**

0.500 inches

# Grip Length:

Between 4.360 inches and 4.390 inches

## Features Provided:

Finished head

# Thready Qty Per Inch (tpi):

20

# Hardness Rating:

248.0 brinell hultgren and 341.0 brinell hultgren

#### Material:

Iron alloy 660

# **Material Specification:**

Ams5731 assn standard single material response or ams5732 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

# **Thread Series Designator:**

Unf

# **Specification Data:**

80205-nas1008 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5306-00-481-9808

Machine Bolt - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-5002 spec.

