NSN 5306-00-482-0946

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-482-0946

View Online at https://aerobasegroup.com/nsn/5306-00-482-0946
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.589 inches and 0.609 inches
Fastener Length:
4.474 inches
Head Style:
Double hexagon w/hole
Head Height:
0.348 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
0.082 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 3.865 inches and 3.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Material:
Steel comp 8740 or steel comp 4140 or steel comp e4340 or steel comp 6150
Material Specification:
Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-5000 military
specification 3rd material response or mil-s-8503 military specification 4th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

NSN 5306-00-482-0946

Shear Bolt - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.