## NSN 5306-00-483-6293

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-483-6293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.781 inches and 0.844 inches **Fastener Length:** Between 3.109 inches and 3.172 inches **Head Style:** Dee chamfer **Head Diameter:** Between 0.855 inches and 0.885 inches **Head Height:** Between 0.271 inches and 0.291 inches **Distance From Centerline To Flat:** Between 0.375 inches and 0.385 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Concentric Hole Depth:** Between 2.344 inches and 2.406 inches **Counterbore Diameter:** Between 0.501 inches and 0.508 inches **Counterbore Depth:** Between 0.068 inches and 0.093 inches **Concentric Hole Diameter:** 0.188 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.271 inches first hole and 3.291 inches first hole Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Style Designator:** Counterbore unthreaded

Unf

**Thread Series Designator:** 

## NSN 5306-00-483-6293

Internally Relieved Body Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0