

View Online at <https://aerobasegroup.com/nsn/5306-00-484-4395>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.611 inches

**Fastener Length:**

Between 1.784 inches and 1.814 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.319 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

0.050 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.178 inches and 1.198 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Minimum Yield Strength:**

156000 pounds per square inch

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837, type 2, class 2 or 3 military specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.