

View Online at <https://aerobasegroup.com/nsn/5306-00-485-0042>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.196 inches and 0.216 inches

Fastener Length:

Between 0.615 inches and 0.635 inches

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.128 inches and 0.148 inches

First Diameter From Head:

Between 0.088 inches and 0.098 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.399 inches and 0.439 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.093 inches and 0.098 inches

Thready Qty Per Inch (tpi):

32

Material:

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 317 or steel comp 321 or steel comp 324 or steel comp 347 or steel comp 322 or steel comp 316l

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.