

View Online at <https://aerobasegroup.com/nsn/5306-00-486-1798>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.531 inches

Fastener Length:

1.438 inches

Head Style:

Round w/wrench flats

Head Diameter:

0.750 inches

Head Height:

0.188 inches

Width Between Flats:

0.615 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches and 0.116 inches first hole

Thread Diameter:

0.437 inches

Grip Length:

0.907 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.238 inches first hole

Product Name:

Navy special project

Material:

Steel comp d6ac

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837 type 2 military standard single treatment response

Test Data Document:

81349-mil-i-6868 standard (includes industry or association standards, individual manufactureer standards, etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.