

View Online at <https://aerobasegroup.com/nsn/5306-00-486-2568>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.514 inches and 0.574 inches

Fastener Length:

Between 5.404 inches and 5.434 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 4.860 inches and 4.890 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

Minimum Yield Strength:

85000 pounds per square inch

Material:

Iron alloy 660 or steel

Material Specification:

Ams 5732 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.