## NSN 5306-00-486-3537

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-486-3537 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.503 inches and 0.553 inches **Fastener Length:** Between 1.763 inches and 1.793 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Shank Unthreaded Hole Diameter:** 0.106 inches and 0.116 inches first hole **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.555 inches and 1.605 inches first hole **Product Name:** Navy special project Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6408 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5306-00-486-3537

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0