

View Online at <https://aerobasegroup.com/nsn/5306-00-487-4746>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.506 inches and 0.556 inches

**Fastener Length:**

Between 1.016 inches and 1.046 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.254 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.465 inches and 0.475 inches

**Extended Washer Thickness:**

0.042 inches

**Hole Diameter:**

0.037 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**End Application:**

Aircraft, f-111 (fms only); helicopter, chinook, ch-47

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Hole Configuration Style:**

Round longitudinal hole

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837 type 1 class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

56878-ewb26 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.