## NSN 5306-00-487-4794

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-487-4794

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.267 inches and 0.334 inches
Fastener Length:
Between 1.652 inches and 1.699 inches
Head Style:
Double hexagon
Head Height:
0.164 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Grip Diameter:
Between 0.2483 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.036 inches first hole
Thread Diameter:
0.250 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.539 inches first hole and 1.571 inches first hole
Material:
Steel comp h11
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-00-487-4794

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0