

View Online at <https://aerobasegroup.com/nsn/5306-00-487-4890>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.374 inches and 0.441 inches

Fastener Length:

Between 1.384 inches and 1.431 inches

Head Style:

Double hexagon

Head Height:

0.210 inches

Width Between Flats:

Between 0.553 inches and 0.564 inches

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 0.990 inches and 1.010 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.251 inches first hole and 1.283 inches first hole

Material:

Steel

Material Specification:

M-107, standard pressed steel co mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0