

View Online at <https://aerobasegroup.com/nsn/5306-00-488-3868>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.625 inches and 0.672 inches

Eye Inside Diameter:

Between 0.375 inches and 0.378 inches

Shoulder Thickness:

0.094 inches

Shank Length:

Between 4.437 inches and 4.484 inches

Eye Stock Thickness:

Between 0.183 inches and 0.193 inches

Shoulder Diameter:

0.750 inches

Ring Stock Diameter:

0.375 inches

Ring Inside Diameter:

2.000 inches

Overall Length:

Between 5.453 inches and 5.500 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

Distance From Center Of Eye To Shank End:

Between 5.029 inches and 5.079 inches

Eye Outside Width:

0.750 inches

Product Name:

Navy special project

Special Features:

Ring material mil-s-6758 cond d, paint interior green

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 5300 assn standard 6th material response

Surface Treatment:

Paint and cadmium

Surface Treatment Specification:

Mil-p-6889 military specification 1st treatment response and qq-p-416 federal specification 2nd treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.