## NSN 5306-00-489-1333



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-489-1333 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.541 inches and 0.581 inches **Fastener Length:** Between 1.251 inches and 1.281 inches **Head Style:** Undercut hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.700 inches and 0.710 inches Thready Qty Per Inch (tpi): 24 **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 or type 3 cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:** 

## NSN 5306-00-489-1333

Close Tolerance Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.