

View Online at <https://aerobasegroup.com/nsn/5306-00-490-4588>

Thread Direction:

Right-hand

Thread Length:

Between 0.848 inches and 0.898 inches

Fastener Length:

Between 1.733 inches and 1.763 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.603 inches and 0.629 inches

Width Between Flats:

Between 0.682 inches and 0.691 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

Between 0.130 inches and 0.160 inches

Hole Diameter:

0.050 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Hole Quantity:

4

Hole Type:

Drilled

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

37.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Special Features:

Four angular slots in head 0.050 in. Wide by 0.010 in. Deep. Asymmetric threads sps-t-282 fscm 56878

Material:

Steel comp e4340 or steel comp 8740

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0