NSN 5306-00-491-9356

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-491-9356

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.489 inches and 0.509 inches |
| Fastener Length: |
| Between 1.765 inches and 1.812 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.203 inches and 0.234 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.234 inches and 1.266 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification all treatment responses |
| Thread Series Designator: |
| Unf |

NSN 5306-00-491-9356

Machine Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0