

View Online at <https://aerobasegroup.com/nsn/5306-00-492-3063>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.399 inches

**Fastener Length:**

Between 2.384 inches and 2.414 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.702 inches and 0.722 inches

**Width Between Flats:**

1.200 inches

**Extended Washer Diameter:**

Between 1.580 inches and 1.590 inches

**Extended Washer Thickness:**

Between 0.230 inches and 0.250 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.9980 inches and 0.9990 inches

**Thread Diameter:**

1.000 inches

**Grip Length:**

1.000 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Steel comp h11

**Material Specification:**

Ams-6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837 type 2, class 2 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.