NSN 5306-00-492-6530

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-492-6530

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.490 inches and 0.557 inches
Fastener Length:
Between 1.500 inches and 1.547 inches
Head Style:
Double hexagon
Head Height:
0.281 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4982 inches and 0.4991 inches
End Application:
Fms- aircraft, hawkeye e-2c; aircraft, tomcat f-14; aircraft, hawkeye e-2c; prowler ea-6b aircraft
Thread Diameter:
0.500 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
M-107, fscm 56878 mfr ref single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-00-492-6530

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0