NSN 5306-00-492-6982

Shear Bolt - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.521 inches and 0.571 inches

Fastener Length:

Between 2.031 inches and 2.061 inches

Head Style:

Double hexagon w/hole

Head Height:

0.254 inches

Width Between Flats:

Between 0.304 inches and 0.315 inches

Extended Washer Diameter:

Between 0.465 inches and 0.475 inches

Extended Washer Thickness:

0.042 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 1.490 inches and 1.510 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

260000 pounds per square inch

Material:

Steel comp h11

Material Specification:

Stsbs003, fscm 98897 mfr ref single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Stsbs003, fscm 98897 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-00-492-6982

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

