NSN 5306-00-494-7319

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-494-7319 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.901 inches and 0.951 inches **Fastener Length:** Between 2.161 inches and 2.191 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.940 inches and 0.950 inches **Extended Washer Thickness:** 0.098 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8831, type 1, cl 2 military specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-00-494-7319

Shear Bolt - Page 2 of 2



	• -		
In	ıŧ	()t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8831 spec.