Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-495-3271



**Thread Class:** 

1a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.429 inches and 0.500 inches

## Fastener Length:

0.500 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.330 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

### **Extended Washer Diameter:**

0.438 inches

### **Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.048 inches

**Thread Diameter:** 

0.250 inches

**Hole Quantity:** 

4

## Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

130000 pounds per square inch

#### Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

### Minimum Yield Strength:

85000 pounds per square inch

## Hole Configuration Style:

Double hexagon longitudinal hole

# Surface Finish:

63.0 microinches bearing surface of head

Material:

Iron alloy 660

# NSN 5306-00-495-3271

Machine Bolt - Page 2 of 2



Material Specification:

Ams 5735 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0