Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-495-6868

т	hread Class:
2	a
Т	hread Direction:
R	light-hand
Т	hread Length:
0	.562 inches
F	astener Length:
2	.125 inches
Н	lead Style:
Н	lexagon
Н	lead Height:
0	.250 inches
V	Vidth Between Flats:
В	etween 0.362 inches and 0.375 inches
F	irst Diameter From Head:
В	etween 0.151 inches and 0.161 inches
S	econd Diameter From Head:
В	etween 0.370 inches and 0.380 inches
D	istance From Largest Bearing Surface Of Head To End Of First Diameter:
0	.188 inches
D	istance From Largest Bearing Surface Of Head To End Of Second Diameter:
0	.375 inches
т	hread Diameter:
0	.250 inches
т	hready Qty Per Inch (tpi):
2	0
E	xternally Relieved Body Diameter Quantity:
2	
N	laterial:
Ν	lickel alloy r-405
N	laterial Specification:
C	Qq-n-281 cl b federal specification single material response
Т	hread Series Designator:
U	Inc
S	helf Life:
Ν	l/a
U	Init Of Measure:
D	emilitarization:
Ν	lo
F	iig:
۸	.003b0