NSN 5306-00-496-9493

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-496-9493

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.205 inches and 1.282 inches |
| Fastener Length: |
| Between 1.265 inches and 1.312 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.281 inches |
| Width Between Flats: |
| Between 0.552 inches and 0.564 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.375 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Material: |
| Steel comp 4140 or steel comp 4130 |
| Material Specification: |
| Mil-s-5626 military specification 1st material response or mil-s-6758 military specification 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2cl3 federal specification all treatment responses |
| Thread Series Designator: |
| Unf |

NSN 5306-00-496-9493

Machine Bolt - Page 2 of 2



| N/a |
|-------------------|
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Shelf Life:

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.