## NSN 5306-00-497-0771

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-497-0771 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.624 inches **Fastener Length:** Between 1.442 inches and 1.472 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.405 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** Between 0.715 inches and 0.725 inches **Extended Washer Thickness:** Between 0.065 inches and 0.085 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 2, class 3 military specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5306-00-497-0771

Shear Bolt - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.