NSN 5306-00-497-9655

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-497-9655 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 2.000 inches **Fastener Length:** 2.810 inches **Head Style:** Round w/wrench flats **Head Diameter:** 1.500 inches **Head Height:** 0.380 inches Width Between Flats: 0.620 inches First Diameter From Head: 0.625 inches **Second Diameter From Head:** 0.480 inches **Third Diameter From Head:** 0.625 inches **Fourth Diameter From Head:** 0.438 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.870 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.370 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.310 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.810 inches **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 35.0 rockwell c **Externally Relieved Body Diameter Quantity:**

2

Material:

Steel comp 4150

NSN 5306-00-497-9655

Fiig: A003b0

Externally Relieved Body Bolt - Page 2 of 2



Material Specification:
Qq-s-624 federal specification all material responses
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No