Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-499-2972

| Thread Class: | |
|-------------------------------|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.410 inches and 0 |).430 inches |
| Fastener Length: | |
| 1.800 inches | |
| Head Style: | |
| Hexagon | |
| Head Height: | |
| Between 0.150 inches and 0 |).163 inches |
| Width Between Flats: | |
| Between 0.428 inches and 0 |).438 inches |
| First Diameter From Head: | |
| Between 0.170 inches and 0 | 0.180 inches |
| Distance From Largest Be | aring Surface Of Head To End Of First Diameter: |
| Between 1.370 inches and 1 | |
| Thread Diameter: | |
| 0.250 inches | |
| Thready Qty Per Inch (tpi): | : |
| 20 | |
| Externally Relieved Body | Diameter Quantity: |
| 1 | |
| Material: | |
| Steel comp 302 or steel cor | np 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| Material Specification: | |
| 66 federal standard all mate | rial responses |
| Surface Treatment: | |
| Passivate | |
| Surface Treatment Specifi | cation: |
| Qq-p-35 federal specification | n single treatment response |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |