

View Online at <https://aerobasegroup.com/nsn/5306-00-500-3375>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.413 inches and 0.463 inches

Fastener Length:

Between 5.548 inches and 5.578 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.076 inches and 0.086 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 5.115 inches and 5.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.356 inches and 5.406 inches first hole

Surface Finish:

32.0 microinches threads

Product Name:

Navy special project

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6305 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0