

View Online at <https://aerobasegroup.com/nsn/5306-00-501-9873>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.413 inches and 0.463 inches

**Fastener Length:**

Between 1.235 inches and 1.265 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.043 inches first hole and 1.093 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6305 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0