

View Online at <https://aerobasegroup.com/nsn/5306-00-505-3262>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.627 inches and 0.677 inches

**Fastener Length:**

Between 2.387 inches and 2.417 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.438 inches and 0.453 inches

**Width Between Flats:**

Between 1.239 inches and 1.252 inches

**Grip Diameter:**

Between 0.8735 inches and 0.8740 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 1.740 inches and 1.760 inches

**Thready Qty Per Inch (tpi):**

14

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.243 inches first hole and 2.293 inches first hole

**Surface Finish:**

63.0 microinches grip

**Material:**

Titanium alloy uns r54520

**Material Specification:**

Nas621, comp 6al-4v assn standard single material response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1264 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0