

View Online at <https://aerobasegroup.com/nsn/5306-00-505-3277>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.345 inches and 0.395 inches

**Fastener Length:**

Between 1.167 inches and 1.197 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.987 inches first hole and 1.037 inches first hole

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6404 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0