NSN 5306-00-505-4099

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-505-4099

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.413 inches and 0.463 inches
Fastener Length:
Between 11.423 inches and 11.453 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Unthreaded Hole Diameter:
0.076 inches and 0.086 inches first hole
Thread Diameter:
0.312 inches
Grip Length:
Between 10.990 inches and 11.010 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
11.231 inches and 11.281 inches first hole
Product Name:
Navy special project
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6405 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-00-505-4099

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0