NSN 5306-00-508-2525

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-2525

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.788 inches and 0.838 inches
Fastener Length:
Between 3.173 inches and 3.203 inches
Head Diameter:
Between 0.740 inches and 0.750 inches
Head Height:
0.438 inches
Hole Diameter:
0.055 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.438 inches
Width Across Flats:
Between 0.313 inches and 0.315 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
34.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Round
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
On-n-416 type 2 cl 2 federal specification all treatment responses

Unf

Thread Series Designator:

NSN 5306-00-508-2525

Internal Wrenching Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

Mil-std (military Standard):

Mil-s-5626 spec.

Shelf Life: