NSN 5306-00-508-2832

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-2832

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.731 inches and 0.751 inches
Fastener Length:
3.241 inches
Head Style:
Double hexagon w/hole
Head Height:
0.435 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
0.099 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 2.490 inches and 2.510 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-00-508-2832

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0